

OUTPUT	POLE	SYN. SPEED	VOLT.	FREQ.	INSUL.	TIME RATING	MODEL	FRAME NO.
3HP	2P	1800 R.P.M	230/460 <sup>V</sup>	60 <sup>Hz</sup>	F	CONT.	TEFC	#182TC
	4P	1800 R.P.M						

\* FOR DIRECT COUPLING  
\* COLOR: MUNSELL RAL 5010  
\* IP55

X	T	BF	BB	BD	AK
0.71	1.63	1/2-13	0.25	9.00	8.50

MOUNTING				A	B	C	D	G	J	O	AH	P	AJ
E	2F	H	BA										
3.75	4.50	0.41	2.75	8.66	5.59	14.43	4.50	0.56	1.57	9.27	2.62	9.55	7.250

AC	KEY			KEYSEAT	CONDUIT BOX			SHAFT EXTENSION			BEARING NO.		APR. WT. (LBS.)
	WIDTH	THICKNESS	LENGTH	R	AS	AA	AB	N-W	U	V	D.E	O.D.E	
5.91	0.250	0.250	1.750	0.986	3.71	NPT3/4"	7.32	2.75	1.125	2.70	6207zz	6206zz	116

NOTE: 1. TOLERANCE OF SHAFT END DIAMETER U: +0.000inch, -0.0005inch  
2. TOLERANCE OF SHAFT CENTER HEIGHT D: +0.00inch, -0.003inch